

ARW Aerowipes

ARW has been designed for the removal of uncured and semi-cured adhesive and polysulphide sealants commonly found in the aerospace and automotive industries. Available as impregnated non-woven, lint-free wipes or liquid form for direct application, they may also be used for general cleaning and degreasing applications. They are ideal for cleaning the tools used to apply sealants and adhesives.

- Removes uncured and semi-cured adhesive and polysulphide sealants; can be used for degreasing
- Available in liquid and wipe form; versatile product to suit many production requirements
- Wipes are non-woven and lint-free; wipe construction also aids the cleaning process
- Non-flammable, water-based product; fluid will evaporate quickly leaving a residue-free finish

Approvals	RoHS Compliant (2015/863/EU):	Yes
Typical Properties	Density @ 20°C (g/ml)	1
	pH	5.5-6.5
Wipe Properties	Fabric Type	41gsm non-woven
	Size	≈ 220 x 375mm
	Quantity	300 impregnated wipes per tub

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
<u>Aerowipes</u>	300 Wipes 500mLliquid	ARW300 ARW500ML	12 Months 48 Months

Directions for Use

Wear protective gloves. Pull out wipe and tear at perforation or when using liquid form, spray onto a wipe or directly onto the surface. Remove the uncured polysulphide sealant or adhesive by wiping the surface until it is totally clean. Testing of sensitive substrates is advised prior to full scale use.

Revision 3: Jan 2020